

testo 174

Mini data logger

The testo 174 mini temperature data logger is ideal for accompanying transports. The logger is simply placed beside the product e.g. in aeroplanes, containers, refrigerated rooms etc. and constantly monitors the fluctuations in temperature unobtrusively.

- ◆ Secure Data - even if battery is spent
- ◆ Current reading is shown on large display
- ◆ Data upload to PC or notebook via interface (optional)
- ◆ Fast data transfer - Data is read out from memory in 10 s.



testo 174, Mini temperature data logger, 1 channel, incl. wall holder, lock and battery

Part no.
0563 1741

Technical data

Probe type	NTC
Meas. range	-30 to +70 °C
Accuracy ±1 digit	±0.5 °C (-20 to +39.9 °C) ±0.8 °C (remaining range)
Resolution	0.1 °C
Oper. temp.	-30... +70 °C
Storage temp.	-40... +70 °C
Battery type	3V button cell (CR 2032)
Battery life	500 days (typical)
Protection class	IP65
Measuring rate	1 min to 4 h (selectable)

Memory	3900 readings
Display	LCD, 1 line
Weight	24 g
Dimensions	55 x 35 x 14 mm
Battery life: 500 days (typical)	
Meas. rate: 1 min to 4 h (selectable)	
Software: Microsoft Windows 95b / 98 / ME / NT2-Sp4 / 2000 / XP	

Set	Part no.
testo 174 Mini temperature data logger, 1 channel, ComSoft 3 Basic, wall holder, lock, interface incl. PC connection cable, battery	0563 1742
Mini temperature data logger, 1 channel, ComSoft 3 Basic, wall holder, USB interface with PC connection cable and battery	0563 1743
Accessories	Part no.
Spare Li battery for testo 174 data logger	0515 0028
Transport case for up to 10 testo 174 data loggers and accessories	0516 1740
ComSoft 3 - Professional with data management, incl. database, analysis and graphics function, data analysis, trend curve	0554 0830
Interface, suitable for testo 174 data logger, incl. PC connection cable	0554 1746
USB interface, suitable for testo 174 data logger, incl. PC connection cable	0554 1739
ISO calibration certificate/temperature, temperature data logger, calibration points -18°C, +60°C	0520 0443